

## Two Glass Swing Door Tropical BackBar Remote

Range: BackBar

SKOPE ID: BB502

Dimensions: 1485 mm (W) × 590 mm (D) × 1025 mm (H)\*

Capacity: 410 L

Project: \_\_\_\_\_

Item #: \_\_\_\_\_

\* Height with castors is adjustable from 1015 to 1035.



A glass door under-bar fridge designed to merchandise ready-to-serve cold beverages in bars, restaurants, clubs, pubs, and cafés. Engineered to serve cold drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 40°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The “frameless” glass doors provide maximum product viewing and are designed for condensation protection in most environments via the double-glazed, argon-filled low-e insulated panels and heated fascia. For high humidity tropical environments heated glass versions are available. The doors and cabinet are fitted with built-in retractable tabs to enable locking via padlock. The built-in LED lights provide optimum merchandising. This fridge is designed to be fitted to a remote refrigeration unit (supplied by others) running on R134a, R404A, or as specified at the time of order. The fridge comes fitted with a thermal expansion valve, solenoid valve, and ball valves. It has copper liquid and suction loops to be connected to the remote unit. Other valve options are available on order. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty



GEMS

© 2022 SKOPE Industries Limited | We reserve the right to alter specifications without notice.


Email: [skope@skope.com](mailto:skope@skope.com)

AUS Freephone: 1800 121 535

NZ Freephone: 0800 947 5673

[skope.com](http://skope.com)



**Cabinet**

Type	BackBar	
Finish	Powder-coated galvanised steel or stainless steel	
Insulation	Type	PU foam
	Thickness (mm)	50
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)
Doors	Type	Glass swing door (double-glazed, heated glass)
	Opening Size	Height (mm) 730
		Width (mm) 460
Shelving	Four adjustable height powder-coated wire shelves 4 × outer shelf (497W × 440D)	
Lighting	1 × 16 W dimmable, cool white (5500-6500K) LED strip on cabinet ceiling	

**Dimensions†**

	External	Internal	Packed
Width (mm)	1485	1020	TBC
Depth (mm)	590	530	TBC
Height (mm)	1015 to 1035 (standard castors) 920 (plinth mount)	758	TBC
Weight (kg)	172		TBC
Capacity (L)	410		
Footprint (m <sup>2</sup> )	0.88		

**Ventilation/Clearance (mm)**

Take into account remote services location.

Top	Not required	Sides	Not required	Rear	Not required
-----	--------------	-------	--------------	------	--------------

**Product Loading**

Facing	330 ml can	28	600 ml bottle	28
Loading	330 ml can	168	600 ml bottle	168

**Dimensional Tolerances**

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet		Multiple cabinets	
			At each joint	At each end wall
Less than 1 metre	±5 mm		±5 mm	+15 mm
More than 1 metre	-5 mm to +10 mm		-5 mm to +10 mm	+15 mm

**Performance**

Product Temperature Range (°C)	1 to 4 (adjustable from 0 to 15)
Maximum Ambient Temperature (°C)	40
Sound Level (dB(A))	Standard < 60
	Hush Mode < 60

**Greenhouse and Energy Minimum Standards (GEMS)**

Star Rating	TBC
Product Temperature Class	M1 (-1 to 5°C)
Total Energy Consumption	6.36 kWh/24 h
Annual Running Costs	\$696 (@ \$0.30/kWh)

**Electrical**

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	1.9 power cord with 3-pin, 10 amp plug
Current Draw (A)	2.0

**Remote Services**

Location	Rear or base
Drain Size	OD 19 mm
Pipe Connection	Liquid line OD 6.35 mm Suction line OD 9.52 mm

**Refrigeration**

Controller	SCS Connect
System Type	Remote cartridge
Cartridge Weight (kg)	16
Refrigerant/Charge	Thermostatic expansion valve fitted to suit refrigerant (R134a or R404A standard)/Nitrogen holding charge
Nominal Capacity (W)	n.a.
Heat Rejection (W)	Average n.a. Peak n.a.
Remote Duty (W)	410
Defrost Type	Automatic, off-cycle

BB.2.GSW.Tr  
on the SKOPE website