

Three Solid Swing Door BackBar Remote

Range: BackBar

SKOPE ID: BB403S

Dimensions: 2045 mm (W) × 590 mm (D) × 1025 mm (H)*

Capacity: 635 L

Project: _____

Item #: _____

* Height with castors is adjustable from 1015 to 1035.




A solid door under-bar fridge designed to merchandise ready-to-serve cold beverages and food in bars, restaurants, clubs, pubs, and cafés. With M1 compliance it is engineered to serve cold food and drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 40°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The doors and cabinet are fitted with built-in retractable tabs to enable locking via padlock. This fridge is designed to be fitted to a remote refrigeration unit (supplied by others) running on R134a, R404A, or as specified at the time of order. The fridge comes fitted with a thermal expansion valve, solenoid valve, and ball valves. It has copper liquid and suction loops to be connected to the remote unit. Other valve options are available on order. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty



GEMS



Cabinet

| | | | |
|------------|--|---------------------------------|-----|
| Type | BackBar | | |
| Finish | Powder-coated galvanised steel or stainless steel | | |
| Insulation | Type | PU foam | |
| | Thickness (mm) | 50 | |
| | Blowing Agent | Cyclo-iso pentane (C5H10/C5H12) | |
| Doors | Type | Solid swing door | |
| | Opening Size | Height (mm) | 730 |
| | | Width (mm) | 460 |
| Shelving | Six adjustable height powder-coated wire shelves 4 × outer shelf (497W × 440D), 2 × inner shelf (555W × 440D) | | |
| Lighting | 1 × 24 W dimmable, cool white (5500-6500K) LED strip on cabinet ceiling | | |

Dimensions†

| | External | Internal | Packed |
|-----------------------------|---|----------|--------|
| Width (mm) | 2045 | 1580 | 2050 |
| Depth (mm) | 590 | 530 | 595 |
| Height (mm) | 1015 to 1035 (standard castors) 920 (plinth mount) | 758 | 1048 |
| Weight (kg) | 212 | | TBC |
| Capacity (L) | 635 | | |
| Footprint (m ²) | 1.21 | | |

Ventilation/Clearance (mm)

Take into account remote services location.

| Top | Not required | Sides | Not required | Rear | Not required |
|-----|--------------|-------|--------------|------|--------------|
|-----|--------------|-------|--------------|------|--------------|

Product Loading

| | | | | |
|---------|------------|-----|---------------|-----|
| Facing | 330 ml can | 44 | 600 ml bottle | 42 |
| Loading | 330 ml can | 264 | 600 ml bottle | 252 |

Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

| Linear dimensions | Single cabinet | | Multiple cabinets | |
|-------------------|-----------------|--|-------------------|------------------|
| | | | At each joint | At each end wall |
| Less than 1 metre | ±5 mm | | ±5 mm | +15 mm |
| More than 1 metre | -5 mm to +10 mm | | -5 mm to +10 mm | +15 mm |

Performance

| | | | |
|----------------------------------|----------------------------------|------|--|
| Product Temperature Range (°C) | 1 to 4 (adjustable from 0 to 15) | | |
| Maximum Ambient Temperature (°C) | 40 | | |
| Sound Level (dB(A)) | Standard | < 60 | |
| | Hush Mode | < 60 | |

Greenhouse and Energy Minimum Standards (GEMS)

| | | | |
|---------------------------|----------------------|--|--|
| Star Rating | n.a. | | |
| Product Temperature Class | M1 (-1 to 5°C) | | |
| Total Energy Consumption | 3.79 kWh/24 h | | |
| Annual Running Costs | \$415 (@ \$0.30/kWh) | | |

Electrical

| | | | |
|------------------|---|--|--|
| Supply | 220 to 240 volts a.c., 50 Hz, single phase supply | | |
| Cord | 1.9 power cord with 3-pin, 10 amp plug | | |
| Current Draw (A) | 2.0 | | |

Remote Services

| | | | |
|-----------------|--------------|------------|-------------------------|
| Location | Rear or base | | |
| Drain Size | OD 19 mm | | |
| Pipe Connection | Liquid line | OD 6.35 mm | Suction line OD 9.52 mm |

Refrigeration

| | | | |
|-----------------------|---|------|-----------|
| Controller | SCS Connect | | |
| System Type | Remote cartridge | | |
| Cartridge Weight (kg) | 16 | | |
| Refrigerant/Charge | Thermostatic expansion valve fitted to suit refrigerant (R134a or R404A standard)/Nitrogen holding charge | | |
| Nominal Capacity (W) | n.a. | | |
| Heat Rejection (W) | Average | n.a. | Peak n.a. |
| Remote Duty (W) | 450 | | |
| Defrost Type | Automatic, off-cycle | | |



BB.3.SSW.r
on the SKOPE website