

Three Solid Swing Door CounterLine Remote

Range: BackBar

SKOPE ID: CL403S

Dimensions: 2195 mm (W) × 680 mm (D) × 830 mm (H)*

Capacity: 533 L

Project: _____

Item #: _____

* Height with castors is adjustable from 820 to 840.



A solid door under-bar fridge designed to merchandise ready-to-serve cold beverages and food in bars, restaurants, clubs, pubs, and cafés. With M1 compliance it is engineered to serve cold food and drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 40°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The doors and cabinet are fitted with built-in retractable tabs to enable locking via padlock. This fridge is designed to be fitted to a remote refrigeration unit (supplied by others) running on R134a, R404A, or as specified at the time of order. The fridge comes fitted with a thermal expansion valve, solenoid valve, and ball valves. It has copper liquid and suction loops to be connected to the remote unit. Other valve options are available on order. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty



GEMS

© 2022 SKOPE Industries Limited | We reserve the right to alter specifications without notice.


Email: skope@skope.com

AUS Freephone: 1800 121 535

NZ Freephone: 0800 947 5673

skope.com





Cabinet

Type	CounterLine		
Finish	Powder-coated galvanised steel or stainless steel		
Insulation	Type	PU foam	
	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)	
Doors	Type	Solid swing door	
	Opening Size	Height (mm)	538
		Width (mm)	511
Shelving	Six adjustable height powder-coated wire shelves 2 × inner shelf (547W × 530D), 4 × outer shelf (605W × 530D)		
Lighting	1 × 24 W, cool white (5500-6500K) LED strip on cabinet ceiling		

Dimensions†

	External	Internal	Packed
Width (mm)	2195	1730	TBC
Depth (mm)	680	565	TBC
Height (mm)	820 to 840 (standard castors)	545	TBC
	725 (plinth mount)		
Weight (kg)	224	TBC	
Capacity (L)	533		
Footprint (m ²)	1.49		

Ventilation/Clearance (mm)

Take into account remote services location.

Top	Sides	Rear
Not required	Not required	Not required

Product Loading

	330 ml can	52	600 ml bottle	46
Facing				
Loading		416		322

Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet		Multiple cabinets	
			At each joint	At each end wall
Less than 1 metre	±5 mm	±5 mm	+15 mm	
More than 1 metre	-5 mm to +10 mm		+15 mm	

Performance

Product Temperature Range (°C)	1 to 4 (adjustable from 0 to 15)		
Maximum Ambient Temperature (°C)	40		
Sound Level (dB(A))	Standard	< 60	
	Hush Mode	< 60	

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	n.a.		
Product Temperature Class	M1 (-1 to 5°C)		
Total Energy Consumption	3.24 kWh/24 h		
Annual Running Costs	\$355 (@ \$0.30/kWh)		

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply		
Cord	1.9 power cord with 3-pin, 10 amp plug		
Current Draw (A)	2.0		

Remote Services

Location	Rear or base		
Drain Size	OD 19 mm		
Pipe Connection	Liquid line	OD 6.35 mm	Suction line OD 9.52 mm

Refrigeration

Controller	SCS Connect		
System Type	Remote cartridge		
Cartridge Weight (kg)	16		
Refrigerant/Charge	Thermostatic expansion valve fitted to suit refrigerant (R134a or R404A standard)/Nitrogen holding charge		
Nominal Capacity (W)	n.a.		
Heat Rejection (W)	Average	n.a.	Peak n.a.
Remote Duty (W)	350		
Defrost Type	Automatic, off-cycle		



CL.3.SSW.r
on the SKOPE website