

specifications




CC300r-2SW

SKOPE Counterline - Slimline
2 Door (Swing), Remote Fridge

CABINET DIMENSIONS

	External	Internal
Height:	725mm*	545mm
Width:	1455mm	1120mm
Depth:	600mm	485mm
Floor area:	0.87m ²	
Gross volume	335L	

* Height excludes castors or legs



CABINET SPECIFICATIONS

Doors:	Self-closing, double glazed, toughened Low-E safety glass with aluminium extrusion or insulated solid doors
Internal door opening size:	2 door openings: 544mm high x 520mm wide
Shelves:	Adjustable height, white plastic coated, steel wire shelves - two per door
Worktop (optional):	Optional 20mm high stainless steel worktop with 65mm fascia
Electrical safety climate class	5
Internal lighting:	1 x 20W T8 Frosted LED Tube (Ø26 x 900mm, 5500K) - Switched
Electrical:	230-240 Volts a.c. 50 Hz, single phase supply, 0.3 Amps
Temperature range:	+1°C to +4°C
GEMS class	M1
GEMS energy consumption	4.31 kWh/24h
GEMS annual running cost	\$472 p.a. (@ \$0.30/kWh)
Refrigeration system:	Side mounted, remote refrigeration unit
Electronic controller:	SKOPE CAREL ir33
Refrigerant:	Selected at time of order: R134a, R404A, R507, R22
Pipe connection size:	Liquid line: 1/4". Suction line: 3/8"
Remote refrigeration duty:	400 Watts
Insulation:	50mm polyurethane foam
Drainage:	Small drain supplied. Must be connected to permanent drain by installer.

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2007 SKOPE Industries Limited

PSS0068 Rev. 4.2 Mar. 2021



SKOPE INDUSTRIES LIMITED

New Zealand Freephone: 0800 947 5673, Australian Freephone: 1800 121 535

Email: skope@skope.com Website: www.skope.com

