



## Cabinet Dimensions:

	External	Internal
Width (mm):	1272	1191
Depth (mm):	836	628
Height (mm):	2204 (std. castors)	1432
Weight (kg):	290	
Capacity (L):	798	
Footprint (m <sup>2</sup> ):	1.07	
Electrical Voltage (V):	220-240	
Electrical Ampere (A):	5.8	
Electrical Frequency (Hz):	50	
MEPS TEC:	22.4	
Refrigerant:	R290 / 150 g	

<b>Dimensional Tolerances</b> Before installing this cabinet allow for the following dimensional tolerances:	
<b>Linear Dimensions</b>	<b>Overall Cabinet Dimensions</b>
Less than 1 metre	+5mm
More than 1 metre	-5mm to +10mm
<b>Length of Multiple Cabinets</b>	
<b>At each joint</b>	<b>At each end wall</b>
+5mm	+15mm
-5mm to +10mm	+15mm

**SKOPE**  
Industries Limited

66 Princess St. PO Box 1091  
Christchurch, New Zealand  
New Zealand Freephone: 0900 947 5673  
Australian Freephone: 1800 121 535  
Email: enquiry@skope.co.nz  
Website: www.skope.co.nz

<b>Model:</b> OD1100N-HS	
<b>Description:</b> Open Deck Open Face POS retail Fridge with Integral, Bottom refrigeration services	
<b>Unless Otherwise Specified:</b> Folded Dimension: Overall Linear Tolerances: ± 0.5mm Angular Tolerances: ± 0.5mm Units: Millimeters	<b>Scale:</b> <b>1 : 20</b>
Copyright © SKOPE Industries Limited	<b>Revision:</b>