specifications



CABINET DIMENSIONS

VF650X

Top Mount,1 Door (Glass), Vertical Freezer



00

2 × rear swivel castors

2 × lockable front swivel castors

| GENERAL SPECIFICATIONS | |
|---------------------------------|--|
| Doors | 1 × self-closing, triple glazed, heated, argon filled, toughened safety glass swing door (hinged RH) |
| Weight | 207 kg |
| Shelves | 5 × adjustable height wire shelves: 625mm wide × 467mm deep |
| Sign | Replacement sign panel. Optional lit sign available with 1 × 11 Watt 600mm T8 LED tube |
| Electrical safety climate class | 5 |
| Internal lighting | 1 × 20 Watt 1400mm LED strip side light |
| Power supply | 220-240 Volts a.c. 50 Hz, single phase supply. Supplied with 10 Amp 3-Pin plug |
| Current draw | 7.5 Amps. |
| Temperature range | -18°C to -21°C |
| GEMS class | L1 |
| GEMS energy consumption | 15.42 kWh/24h |
| GEMS annual running cost | \$1,690 p.a. (@ \$0.30/kWh) |
| Refrigeration system | Top mounted SKOPE Cyclone freezer unit with electronic controller (UF40ACD) (5.3 Amps) |
| Refrigerant | R452A / 700g |
| Nominal capacity | 752 Watts @ -30°C evaporator, 50°C condenser |
| Electronic controller | CAREL ir33 electronic controller |
| Drainage | No plumbing required |

SKOPE Industries Limited reserve the right to alter specifications without notice.Copyright © 2016 SKOPE Industries Limited

PSS0433 Rev.2.0 Aug. 2020



SKOPE INDUSTRIES LIMITED

New Zealand Freephone: 0800 947 5673, Fax: (03) 983 3896. Australian Freephone: 1800 121 535, Freefax: 1800 121 533 Email: enquiry@skope.co.nz Website: www.skope.co.nz