specifications

PG600VFr





CABINET SPECIFICATIONS

Refrigeration system:	Electronic controlled, top mounted, removable remote refrigeration unit
Refrigeration unit model:	UF40AAR
Refrigerant:	Thermostatic expansion valve fitted to suit R404A/R452A
Pipe connection size:	Liquid line: 1/4". Suction line: 3/8"
Remote refrigeration duty:	695 Watts
Cabinet internal volume:	586 litres
Insulation:	60mm thick, high density cyclo-isopentane polyurethane foam
Cabinet temperature range:	-18°C to -21°C up to 43°C ambient
Drainage:	A condensate drain must be run from the cabinet to a waste outlet.
Electrical:	230-240 Volts a.c. 50 Hz, 5.0 Amps
Interior lighting:	1 interior light: 5 Watt T8 LED tube (Ø26 × 360mm) - Door activated
Internal door opening size:	1 door opening: 1520mm high × 565mm wide
Door:	Solid, stainless steel, self-closing door (with key lock) - LH hinged
Shelves:	5 levels of non-tip, adjustable tray slides and/or shelves 530mm × 650mm
Weight:	195 kg

SKOPE Industries Limited reserve the right to alter specifications without notice.

PSS0360 Rev. 1.3 Nov. 2019



SKOPE INDUSTRIES LIMITED

Australian Freephone: 1800 121 535, New Zealand Freephone: 0800 947 5673 Email: enquiry@skope.co.nz, Website: www.skope.com