


Top Mount, 1 Glass Door, Upright Fridge

Range: EziCore
SKOPE ID: ET65BYN
Dimensions: 740 mm (W) × 750 mm (D) × 2210 mm (H)
Capacity: 557 L

Project: _____

Item #: _____



A high-efficiency, top-mounted, one glass door display fridge designed to display and store ready-to-serve chilled food and drinks. It is suitable for a range of front of house applications such as bars, restaurants, clubs, pubs, cafés, convenience stores, supermarkets, and quick service restaurants. The fridge is engineered to serve cold drinks at 0°C to 5°C in ambient environments of up to 35°C and is GEMS-compliant, as well as food-safe with 3M1 climate class. It is made from white powder-coated, galvanised steel, and you can customise the lit sign panel with your own branding. The double-glazed door helps prevent condensation and includes built-in LED lights in the door frame to ensure excellent merchandising of your products. The self-contained fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge and low noise output. The top-mounted refrigeration cartridge can be removed in line with best practice for safe servicing of flammable refrigerants. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty



Natural Refrigerant



GEMS




© 2022 SKOPE Industries Limited | We reserve the right to alter specifications without notice.

Email: skope@skope.com

AUS Freephone: 1800 121 535

NZ Freephone: 0800 947 5673

skope.com

**Cabinet**

| | | | |
|-------------------|--|--|------|
| Type | TCE Fridge | | |
| Finish | Powder-coated galvanised steel | | |
| Insulation | Type | PU foam | |
| | Thickness (mm) | 50 | |
| | Blowing Agent | Cyclo-iso pentane (C5H10/C5H12) | |
| Doors | Type | Glass swing door (double-glazed, argon-filled, toughened safety glass) | |
| | Opening Size | Height (mm) | 1570 |
| | | Width (mm) | 645 |
| Shelving | Four adjustable height plastic-coated wire shelves 4 x full width shelf (620W x 460D) | | |
| Lighting | Sign | 1 x 3 W, 490 mm LED | |
| | Interior | 2 x 6 W, 1360 mm LED in door frame | |

Dimensions†

| | External | Internal | Packed |
|----------------|----------------|----------|--------|
| Width (mm) | 740 | 640 | 755 |
| Depth (mm) | 750 | 554 | 775 |
| Height (mm) | 2210 (castors) | 1570 | 2210 |
| Weight (kg) | 136.6 | | 139.6 |
| Capacity (L) | 557 | | |
| Footprint (m²) | 0.56 | | |

Ventilation (mm)

| Top | 300 | Sides | Not required | Rear | Not required |
|-----|-----|-------|--------------|------|--------------|
|-----|-----|-------|--------------|------|--------------|

Performance

| | | |
|---|----------|-----|
| Product Temperature Range (°C) | 0 to +5 | |
| Maximum Ambient Temperature (°C) | 35 | |
| Sound Level (dB(A)) | Standard | <65 |

Greenhouse and Energy Minimum Standards (GEMS)

| | | |
|----------------------------------|----------------------|--|
| Star Rating | 8 | |
| Product Temperature Class | M1 (-1 to 5°C) | |
| Total Energy Consumption | 3.15 kWh/24 h | |
| Annual Running Costs | \$345 (@ \$0.30/kWh) | |

Electrical

| | | |
|-------------------------|---|--|
| Supply | 220 to 240 volts a.c., 50 Hz, single phase supply | |
| Cord | TBC m power cord with 3-pin, 10 amp plug | |
| Current draw (A) | 3.0 | |

Refrigeration

| | | | |
|------------------------------|-------------------------|-----|----------|
| Controller | Electronic – adjustable | | |
| System Type | Removable cartridge | | |
| Cartridge Weight (kg) | 25.6 | | |
| Refrigerant/Charge | R290/84 g | | |
| Nominal Capacity (W) | 670 (EN12900 MBP) | | |
| Heat Rejection (W) | Average | 130 | Peak 150 |
| Defrost Type | Automatic, off-cycle | | |
| Drainage | No plumbing required | | |

Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

| Linear dimensions | Single cabinet | Multiple cabinets | |
|-------------------|-----------------|-------------------|------------------|
| | | At each joint | At each end wall |
| Less than 1 metre | ±5 mm | ±5 mm | +15 mm |
| More than 1 metre | -5 mm to +10 mm | -5 mm to +10 mm | +15 mm |



TCE650N
on the SKOPE website