

Interior shelf lighting	n.a.	Before installing this cabinet allow the following dimensional tolerances:		
Sign lighting	n.a.			
Power cord	Supplied with 2.3m, 10 Amp plug and lead	Linear dimensions	Overall cabinet dimensions	
Power supply	220-240 Volts a.c. 50 Hz, single phase supply	Less than 1 metre	±5mm -5mm to +10mm	
Current draw	2.9 Amps (includes unit 2.6 Amps)	More than 1 metre		
			Length of multiple cabinets	
REFRIGERATION			At each joint	At each end wall
Controller	SCS Connect (SKOPE-connect [™] compatible)	Less than 1 metre	±5mm	+15mm
Connectivity interface	Bluetooth	More than 1 metre	-5mm to +10mm	+15mm
Refrigeration system	Top mounted, integral, removable ActiveCore refrigeration unit (UTHCNI-0010)	Ventilation requirements		
Refrigerant	R290 / 99g (natural refrigerant)	Тор	300mm	
Nominal capacity	740 Watts	Sides	Not required	
Heat rejection (Avg/peak)	90 Watts/110 Watts	Back	Not required	
Drainage	No plumbing required	Bottom	Not required	

SKOPE Industries Limited reserve the right to alter specifications without notice. Copyright © 2019 SKOPE Industries Limited

SKOPE INDUSTRIES LIMITED

specifications





Refrigeration